



K2 ANTI GRAVEL

BLACK

A fast-drying undercoating based on synthetic resins, forms an elastic, sealed film to protect car body from mechanical factors, rust and water impacts. The product can be painted over using any type of paint, once the film has completely hardened. Suitable for use on thresholds, bumpers, spoilers and other parts.

Directions: Before use, clean, degrease and dry the surface. Mask all the surrounding parts to protect them from unexpected painting. Prior use, shake well for app. 3 minutes to mix the product thoroughly. Use a maintenance gun at the pressure value of 5-8 bar. Apply several strokes for the best results. The surface can be painted with conventional lacquers after 3 hours of drying at 20°C or after 24 hours in case of using water based lacquers. Do not spray on the engine, brake system, muffler or suspension parts.



LOGISTIC DATA

INDEX	CAPACITY	EAN	CN CODE
L315P	1 L	5906534740397	32089019

PCS/ BOX	PCS/ PALLET	BOX WEIGHT	BOX WIDTH	BOX HEIGHT	BOX DEPTH
12	480	13,9 kg	350 mm	245 mm	280 mm

PIECE WEIGHT	PIECE WIDTH	PIECE HEIGHT	PIECE DEPTH
1,13 kg	85 mm	235 mm	85 mm



Visit [www](http://www.melle.com)